

# OUTLAW<sup>®</sup> EXTREME



# BUILT TOUGH

## FOR AUSTRALIAN CONDITIONS.



## EXTREME VALUE FOR ALL-OUT EXTREME PERFORMANCE...



## CLASSIC AMERICAN MUSCLE

This Bad Boy is the definition of extreme and is built specifically for the tough commercial mower market. With the largest integrated transaxle, Hydro-Gear<sup>®</sup> offers a wide range of engine options and lower profile frame. It is a commercial operators' dream machine!

- UP TO 20.9 KM/H MOWING SPEED
- ALL NEW DECK LIFT SYSTEM
- 52 LITRE FUEL CAPACITY
- FOUR-RAIL ALL-WELDED STEEL FRAME
- TWO YEAR WARRANTY\*



Bad Boy Mowers Distributors Pty Ltd  
55-57 Carrington Road, Toowoomba QLD 4350  
PHONE 1300 783 379

AVAILABLE FROM



# MOWER SPECIFICATIONS

## OUTLAW EXTREME MODELS

**993cc****852cc****KOHLER 824ccEFI**

<b>Cutting Width</b>	6100/155 cm; 7200/183 cm	5400/137cm; 6100/155 cm; 7200/183cm	5400/137cm; 6100/155cm
<b>Cutting Height</b>	2.54cm - 13.97cm with Deck Height Control System	2.54cm - 13.97cm with Deck Height Control System	2.54cm - 13.97cm with Deck Height Control System
<b>Blades</b>	6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated 7200/1/4" x 2 1/2" x 24", High Lift, Heat Treated	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated 7200/1/4" x 2 1/2" x 24", High Lift, Heat Treated	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Foot-Assist Manual Deck Lift	Foot-Assist Manual Deck Lift	Foot-Assist Manual Deck Lift
<b>Blade Belt</b>	Single V-Belt Spring Tension	Single V-Belt Spring Tension	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	6 Total ( 4 on the front, 2 on the rear)	6 Total ( 4 on the front, 2 on the rear)	6 Total ( 4 on the front, 2 on the rear)
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	6.35mm Thick Solid Steel	6.35mm Thick Solid Steel	6.35mm Thick Solid Steel
<b>ENGINE</b>			
<b>Gross Horsepower</b>	36hp Air-Cooled Vanguard	27hp Air-Cooled Kawasaki FX	29 EFI - 824cc Air-Cooled Kohler EFI
<b>Cylinders</b>	V-Twin	90 Degree V-Twin	V-Twin
<b>Displacement</b>	993 cc	852 cc	747 cc
<b>Maximum Torque</b>	80 Nm.@ 2600 RPM	60.5 Nm. @ 2400 RPM	61.7 Nm. @ 2600 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	52.5 Litres	52.5 Litres	52.5 Litres
<b>Fuel Filter</b>	Replaceable Automotive Type	Replaceable Automotive Type	Replaceable Automotive Type
<b>Cooling System</b>	Air-Cooled	Air-Cooled	Air-Cooled
<b>Ignition</b>	Electronic	Electronic	Electronic
<b>Starter</b>	12 Volt	12 Volt	12 Volt
<b>Charging System</b>	20 amp	20 amp	20 amp
<b>DRIVE SYSTEM</b>			
<b>Transmission</b>	Industrial Grade Dual Integrated Hydrostatic Transaxle	Industrial Grade Dual Integrated Hydrostatic Transaxle	Industrial Grade Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction
<b>Wheel Drive</b>	Hydro-Gear Integrated 5400 Series Transaxle	Hydro-Gear Integrated 5400 Series Transaxle	Hydro-Gear Integrated 5400 Series Transaxle
<b>Hydrostatic System Oil</b>	20W50 Motor Oil	20W50 Motor Oil	20W50 Motor Oil
<b>Hydraulic Filter</b>	Internal, Replaceable. 1 per axle	Internal, Replaceable. 1 per axle	Internal, Replaceable. 1 per axle
<b>Pumps (2)</b>	Hydro-Gear 16 cc Pump	Hydro-Gear 16 cc Pump	Hydro-Gear 16 cc Pump
<b>Hydraulic Coolers (2)</b>	9" 3600 RPM Cooling Fan: One per Unit	9" 3600 RPM Cooling Fan: One per Unit	9" 3600 RPM Cooling Fan: One per Unit
<b>Weight</b>	6100/557.9kg; 7200/594 kg.	5400/535.2 kg / 6100/557.9 kg/ 7200/594 kg	5400/535.2 kg / 6100/557.9 kg.
<b>Overall Height</b>	121.9cm	121.9cm	121.9cm
<b>Overall Width</b>	6100/158.75 cm; 7200/186.7 cm	5400/141cm / 6100/158.75 cm; 7200/186.7 cm	5400/141 cm / 6100/158.75 cm
<b>Overall Length</b>	218.5 cm	218.5 cm	218.5 cm
<b>Tyre to Tyre Width</b>	6100/142 cm; 7200/152.4cm	5400/132 cm / 6100/142 cm; 7200/152.4 cm"	5400/132 cm / 6100/142 cm
<b>Tyres—Front</b>	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
<b>Tyres—Rear</b>	24x12-12 Turf Tread	24x12-12 Turf Tread	24x12-12 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 20.9 kmh	Up to 20.9 kmh	Up to 20.9 kmh
<b>Parking Brake</b>	Internal Wet Disk	Internal Wet Disk	Internal Wet Disk

**SPECIFICATIONS ARE SUBJECT TO CHANGE. \*(LIMITED WHEN USED IN A COMMERCIAL ENVIRONMENT)**



**BAD BOY MOWERS  
DISTRIBUTORS PTY LTD**

55-57 Carrington Road, Toowoomba QLD 4350 • PHONE 1300 783 379