

If you are looking for the efficiencies of a zero-turn mower at a price that does not compromise on quality build construction and quality of cut – turn to the MZ Magnum. You will appreciate the solid all-welded steel construction, powerful engine and professional ride, cut and performance.

- UP TO 10 KM/H MOWING SPEED
- 3mm SOLID STEEL FABRICATED AND WELDED DECK
- 11 LITRE FUEL CAPACITY
- TWO-RAIL 2" x 2" ALL-WELDED STEEL FRAME
- TWO YEAR WARRANTY\*



Bad Boy Mowers Distributors Pty Ltd 55-57 Carrington Road, Toowoomba QLD 4350 PHONE 1300 783 379 **AVAILABLE FROM** 



## **MOWER SPECIFICATIONS**

## MZ MAGNUM MODEL

## **KOHLER**. **725cc**

| Cutting Width  | <b>4800</b> /121.9cm; <b>5400</b> /137.2cm                     |
|----------------|--|
| Cutting Height | 1"-4" with Deck Height Control System                          |
| Blades         | <b>4800</b> /7/32" x 2 1/2" x 16 1/2", High Lift, Heat Treated |
|                | <b>5400</b> /7/32" x 2 1/2" x 18 1/2", High Lift, Heat Treated |
|                |  |

| Lift and Height Adjustment | Foot-Assist Lift  |
|----------------------------|---|
| Blade Belt                 | Single V-Belt Spring Tension                              |
| Anti-Scalp Rollers         | 2 Total (2 Front)   |
| Deck Flotation             | Floats on 4 Leveling Linkages Along with 2 Anti-Sway Bars |
| Deck Thickness             | 3.175mm Thick Solid Steel                                 |
| ENGINE                     |   |
| Gross Horsepower           | 22hp Air-Cooled Kohler Pro 7000                           |
| Cylinders                  | 90 Degree V-Twin  |
| Displacement               | 725 cc  |
| Maximum Torque             | 56 Nm. @ 2400 RPM   |
| Fuel Requirement           | Unleaded Gasoline (87 Octane or higher)                   |
| Fuel Capacity              | 9.5 Litres  |
| Fuel Filter                | Replaceable Automotive Type                               |
| Cooling System             | Air-Cooled  |
| Ignition                   | Electronic  |
| Starter                    | 12 Volt   |
| Charging System            | 16 amp  |
| DRIVE SYSTEM               |   |
| Transmission               | Dual Integrated Hydrostatic Transaxle                     |
| Pump Drive                 | Integrated Axial Piston Pump & Motor w/Gear Reduction     |
| Wheel Drive                | Integrated with Gear Reduction                            |
| Hydrostatic System Oil     | 20W50 Motor Oil   |
| Hydraulic Filter           | <del>_</del>  |
| Pumps (2)                  | EZT Integrated Unit                                       |
| Hydraulic Coolers (2)      | 7" Cooling Fan per Unit                                   |
| Weight                     | <b>4800</b> /265.4kg; <b>5400</b> /273kg.                 |
| Overall Height             | 106.7cm   |
| Overall Width              | <b>4800</b> /123.2cm"; <b>5400</b> /138.4cm               |
| Overall Length             | 172,1cm   |
| Tyre to Tyre Width         | 109.2cm   |
| Tyres—Front                | 11 x 6.0-5 Smooth Tread                                   |
| Tyres—Rear                 | 18 x 9.5–8 Turf Tread                                     |
| Steering                   | Dual Lever Steering, Independent Control                  |
| Turning Radius             | Zero Degree, Turns Within Unit Length                     |
| Ground Speed (forward)     | Up to 6 mph   |
| Parking Brake              | External Cogg Brake                                       |

SPECIFICATIONS ARE SUBJECT TO CHANGE. \*(LIMITED WHEN USED IN A COMMERCIAL ENVIRONMENT)



BAD BOY MOWERS DISTRIBUTORS PTY LTD