



SETTING THE STANDARD

LCT SERIES SLASHERS

- TPL Cat and II
- Flex Tower
- Laminated Spring Steel Blades and Beams
- High Speed IBO HP Gearbox
- 4 Plate Clutch Protection
- Rear Stone Guard
- Adjustable Skids
- 300mm Side Depth
- 6mm Clean Top Design
- Side Plates also 6mm
- Front and Rear Safety Chains
- Single 400 x 8 Solid Monofill Castor Wheels for LCT72
- Twin 400 x 8 Solid Monofill Castor Wheels for LCT94

Model	Working Width	Weight	HP (Min.)
LCT72	1.8m (6')	750 kg	60
LCT84	2.15m (7)	850 kg	70
LCT94	2.35m (7'10")	1,000 kg	90

Options

Cat III Tower for LCT, LXCT Sign Rack (complete with 4 signs) Tool Box Support Legs Hydraulic Fan Rear Lights Extra Wheelkit for LCT72 & LXCT6B



FREECALL: 1800 454 150

Phone: (07) 469I I500 Fax: (07) 469I I5II www.fieldquip.com.au I99 Bridge Street Oakey Queensland Australia 440I

> Additional lines may be added or deleted from the range in this guide visit **www.fieldquip.com.au** for new models and availability