

# MZ SERIES



# BUILT TOUGH

## FOR AUSTRALIAN CONDITIONS.



### AFFORDABLE MANEUVERABILITY.

For the first time, the combination of solid steel construction plus incredible priced power, all the hallmarks of a Bad Boy Mower, have been rolled into one durable, fun to drive, inexpensive and easy to operate zero-turn mower.



### CLASSIC AMERICAN MUSCLE

- UP TO 10 KM/H MOWING SPEED
- 3mm SOLID STEEL FABRICATED AND WELDED DECK
- FOOT-ASSIST ADJUSTABLE DECK LIFT
- SOLID STEEL FRONT FORKS
- TWO YEAR WARRANTY\*



Bad Boy Mowers Distributors Pty Ltd  
55-57 Carrington Road, Toowoomba QLD 4350  
PHONE 1300 783 379

AVAILABLE FROM



# MOWER SPECIFICATIONS

## MZ MODELS

**KOHLER. 725cc****540cc**

Cutting Width	106.7cm	106.7cm
Cutting Height	2.54cm-10.16cm with Deck Height Control System	2.54cm-10.16cm with Deck Height Control System
Blades	7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated	7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Lift	Foot-Assist Lift
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	2 Total (2 Front)	2 Total (2 Front)
Deck Flotation	Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars	Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars
Deck Thickness	3.175mm Thick Solid Steel	3.175mm Thick Solid Steel
<b>ENGINE</b>		
Gross Horsepower	22hp - 726cc Air-Cooled Kawasaki FR	19hp - 540cc Air-Cooled Briggs & Stratton
Cylinders	90 Degree V-Twin	Single Cylinder
Displacement	725 cc	540 cc
Maximum Torque	54.2Nm @ 2600 RPM	38 Nm. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	9.5 Litres	9.5 Litres
Fuel Filter	Replaceable Automotive Type	Replaceable Automotive Type
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	16 amp	16 amp
<b>DRIVE SYSTEM</b>		
Transmission	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Gear Reduction	Integrated with Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	—	—
Pumps (2)	EZT Integrated Unit	EZT Integrated Unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit	7" Cooling Fan per Unit
Weight	266kg	266kg
Overall Height	106.7cm	106.7cm
Overall Width	106.7cm	106.7cm
Overall Length	172cm	172cm
Tyre to Tyre Width	104cm	104cm
Tyres—Front	11 x 6.0-5 Smooth Tread	11 x 6.0-5 Smooth Tread
Tyres—Rear	18 x 8.5-8 Turf Tread	18 x 8.5-8 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 9.7 kmh	Up to 9.7 kmh
Parking Brake	External Cogg Brake	External Cogg Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE. \*(LIMITED WHEN USED IN A COMMERCIAL ENVIRONMENT)



BAD BOY MOWERS  
DISTRIBUTORS PTY LTD

55-57 Carrington Road, Toowoomba QLD 4350 • PHONE 1300 783 379