

ZT
ELITE
SERIES



BUILT TOUGH

**FOR AUSTRALIAN
CONDITIONS.**



**CLASSIC
AMERICAN
MUSCLE**

SIMPLY, A BETTER ALL ROUND MOWER...

We set a whole new standard for power, performance and price with the ZT Elite. Virtually every component of the ZT Elite has been improved, giving improved hydraulics, better handling, more comfort and a cleaner cut. Compare and you'll find that there simply is no better value zero-turn mower for the home owner.

- **UP TO 11 KM/H MOWING SPEED AND SHARPER CUTS**
- **HEAVY DUTY CLUTCH**
- **20 LITRE FUEL CAPACITY**
- **TWO-RAIL 2" x 2" ALL-WELDED STEEL FRAME**
- **TWO YEAR WARRANTY***



Bad Boy Mowers Distributors Pty Ltd
55-57 Carrington Road, Toowoomba QLD 4350
PHONE 1300 783 379

AVAILABLE FROM



MOWER SPECIFICATIONS

ZT ELITE MODELS

KOHLER 725cc**KOHLER 747cc****Kawasaki 726cc**

Cutting Width	4800 /121.9cm	5400 /137.2cm; 6000 /152.4cm	4800 /121.9cm; 5400 /137.2cm; 6000 /152.4cm
Cutting Height	3.8cm–10.2cm with Deck Height Control System	13.8cm–10.2cm with Deck Height Control System	3.8cm–10.2cm with Deck Height Control System
Blades	4800 /1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated	5400 /1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6000 /1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated	4800 /1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400 /1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6000 /1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator	Instant Lift Electronic Actuator	Instant Lift Electronic Actuator
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	4800 /4 Total (2 On Front, 2 In Rear)	5400 /4 Total (2 Front, 2 Rear) /6000 /6 Total (4 Front, 2 Rear)	4800 /4 Total (2 On Front, 2 In Rear) 5400 /4 Total (2 Front, 2 Rear) /6000 /6 Total (4 Front, 2 Rear)Floats on 2
Deck Flotation	Floats on 2 Chains & 2 Front Levelling Arms	Floats on 2 Chains & 2 Front Levelling Arms	Chains & 2 Front Levelling Arms
Deck Thickness	4.76mm Thick Solid Steel	4.76mm Thick Solid Steel	4.76mm Thick Solid Steel
ENGINE			
Gross Horsepower	25hp - 725cc Air-Cooled Kohler Pro 7000	26hp - 747cc Air-Cooled Kohler Pro 7000	24hp - 726cc Air-Cooled Kawasaki FR
Cylinders	90 Degree V-Twin	90 Degree V-Twin	90 Degree V-Twin
Displacement	725cc	747 cc	726 cc
Maximum Torque	56Nm. @ 2400 RPM	56Nm. @ 2400 RPM	54.2Nm. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	20.8 Litres	20.8 Litres	20.8 Litres
Fuel Filter	Replaceable In-Line Filter	Replaceable In-Line Filter	Replaceable In-Line Filter
Cooling System	Air-Cooled	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic	Electronic
Starter	12 Volt	12 Volt	12 Volt
Charging System	16 amp	16 amp	20 amp
DRIVE SYSTEM			
Transmission	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Commercial Grade Gear Reduction	Integrated with Commercial Grade Gear Reduction	Integrated with Commercial Grade Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Axle	25 Micron, Replaceable Spin-On Type, 1 Per Axle	25 Micron, Replaceable Spin-On Type, 1 Per Axle
Pumps (2)	10cc Pump and Motor Integrated in one unit	10cc Pump and Motor Integrated in one unit	10cc Pump and Motor Integrated in one unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit	7" Cooling Fan per Unit	7" Cooling Fan per Unit
Weight	4800 /365kg	5400 /377kg; 6000 /390kg.	4800 /365kg; 5400 /377kg; 6000 /390kg.
Overall Height	117cm	117cm	117cm
Overall Width	4800 /126cm	5400 /141cm; 6000 /156.2cm	4800 /126cm; 5400 /141cm; 6000 /156.2cm
Overall Length	189.2cm	189.2cm	189.2cm
Tyre to Tyre Width	117cm	117cm	117cm
Tyres—Front	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
Tyres—Rear	22 x 11–10 Turf Tread	22 x 11–10 Turf Tread	22 x 11–10 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 11.3 kmh	Up to 11.3 kmh	Up to 11.3 kmh
Parking Brake	Internal Parking Brake	Internal Parking Brake	Internal Parking Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE. *(LIMITED WHEN USED IN A COMMERCIAL ENVIRONMENT)



**BAD BOY MOWERS
DISTRIBUTORS PTY LTD**

55-57 Carrington Road, Toowoomba QLD 4350 • PHONE 1300 783 379