

CAT ^{POWERED}
DIESEL



BUILT TOUGH

**FOR AUSTRALIAN
CONDITIONS.**



**OUR BIGGEST MOWER MAY WELL BE
YOUR BIGGEST VALUE.**



**CLASSIC
AMERICAN
MUSCLE**

The legendary durability, power and reliability of a Caterpillar® engine, coupled with our incredible build quality and strength, combines to deliver years of day in, day-out mowing. This Diesel mower represents power and strength, from the heavy duty clutch to the over-sized hydraulic motors and pumps.

- **UP TO 20.9 KM/H MOWING SPEED**
- **SWING AWAY DESIGN ACCESS**
- **81 LITRE FUEL CAPACITY**
- **FOUR-RAIL ALL-WELDED STEEL FRAME**
- **TWO YEAR WARRANTY***



Bad Boy Mowers Distributors Pty Ltd
55-57 Carrington Road, Toowoomba QLD 4350
PHONE 1300 783 379

AVAILABLE FROM



MOWER SPECIFICATIONS

DIESEL MODELS

**1500cc****1100cc**

Cutting Width	6100/ (155cm); 7200/ (183cm)	6100/ (155cm)
Cutting Height	1.5"–5" with Deck Height Control System (3.81cm – 12.7cm)	1.5"–5" with Deck Height Control System (3.81cm – 12.7cm)
Blades	6100/ 1/4" x 2 1/2" x 21", High Lift, Heat Treated 7200/ 1/4" x 2 1/2" x 24", High Lift, Heat Treated	6100/ 1/4" x 2 1/2" x 21", High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator	Foot-Assist Manual and Electric Actuator
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	6 Total (4 on the front, 2 on the rear)	6 Total (4 on the front, 2 on the rear)
Deck Flotation	Floats on 2 Chains & 2 Front Leveling Arms	Floats on (4) 1/4" Deck Hangers
Deck Thickness	6.35mm Thick Solid Steel	6.35mm Thick Solid Steel
ENGINE		
Gross Horsepower	35hp 1500cc Caterpillar Diesel	28hp 1100cc Caterpillar Diesel
Cylinders	4 Diesel	3 Diesel
Displacement	1.5 L. / 4-Cylinder	1.1 L. / 3-Cylinder
Maximum Torque	127Nm, @ 3000 RPM	95Nm, @ 3400 RPM
Fuel Requirement	Diesel	Diesel
Fuel Capacity	68 Litres	68 Litres
Fuel Filter	—	—
Cooling System	Liquid-Cooled	Liquid-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	20 amp	20 amp
DRIVE SYSTEM		
Transmission	Dual Hydrostatic	Dual Hydrostatic
Pump Drive	16 cc Hydro-Gear V-Belt from Engine Crankshaft	16 cc Hydro-Gear V-Belt from Engine Crankshaft
Wheel Drive	18 cu. in. High Torque Parker Motors	18 cu. in. High Torque Parker Motors
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Pump	25 Micron, Replaceable Spin-On Type, 1 Per Pump
Pumps (2)	Hydro-Gear 16cc Pump	Hydro-Gear 16cc Pump
Hydraulic Coolers (2)	System Designed w/2 Coolers for Lower Temperatures	System Designed w/2 Coolers for Lower Temperatures
Weight	6100/ 860 kg; 7200/ 878 kg.	6100/ 729 kg.
Overall Height	133cm	133cm
Overall Width	185cm	185cm
Overall Length	216cm	201cm
Tyre to Tyre Width	6100/ 145cm; 7200/ 155cm	6100/ 145cm
Tyres—Front	13 x 6.5–6 Smooth Treads/No Flats	13 x 6.5–6 Smooth Treads/No Flats
Tyres—Rear	26 x 12–12 Turf Tread	26 x 12–12 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 19.3 km/h	Up to 19.3km/h
Parking Brake	Disk Brakes	Disk Brakes

SPECIFICATIONS ARE SUBJECT TO CHANGE. *(LIMITED WHEN USED IN A COMMERCIAL ENVIRONMENT)



BAD BOY MOWERS
DISTRIBUTORS PTY LTD

55-57 Carrington Road, Toowoomba QLD 4350 • PHONE 1300 783 379